



COMSATS UNIVERSITY ISLAMABAD

DEPARTMENT OF COMPUTER SCIENCE

Final Term Examination, Fall 2024

Class: BCS-V(A/B), BCT-4/5, BDS-5, BAI-5

Date: -----

Subject: Design and Analysis of Algorithm

Instructor: Dr. Maimoona Malik/Mr. Tanveer Ahmed//Mr. Osama Subhani/ Ms. Hilal Jan

Total Time Allowed: 180 minutes

Max Marks: 50

Name: _____

Registration Number: _____

NOTE: Do as directed don't go into extra detail. Only crisp and concise answers will earn you credit

- Students are required to display their ID cards.
- Attempt all questions. **Return this question paper with your answer sheet.**
- Use of Mobile Phones and Digital Diaries not allowed

(CLO-1: Demonstrate fundamental concepts of algorithm along with an algorithmic approach to a given problem.)

Q # 01

Marks = [5+5= 10]

- 1.1. Identify which properties of an algorithm – **input, output, precision, determinism, finiteness, correctness, and generality** – does following procedure have and which is lacking? Justify your answer.

PROCEDURE: Goldbach_Conjecture ()

// The purpose of this procedure is to check whether every even number greater than 2 is the sum of two prime numbers or not.

1. $n \leftarrow 4$
2. **if** ($n \neq (p_1 + p_2)$) **then** // p_1 and p_2 are two prime numbers
3. print “NO”
4. **break**
5. **else**
6. $n \leftarrow n + 2$
7. **goto** 2
8. print “YES”
9. **end**

- 1.2. Trace (Dry run) the following algorithm with $m = 24$ and $n = 60$. Explain what does this algorithm compute?

ALGORITHM Enigma(m, n)

// Input: Two non-negative integers m and n , not both zero.

// Output: Greatest Common Divisor of m and n

- 1 **if** $m = 0$ **then**
- 2 $ans \leftarrow n$
- 3 **else if** $m > n$ **then**
- 4 $ans \leftarrow Enigma(n, m)$
- 5 **else**
- 6 $nLess \leftarrow n - m$
- 7 $ans \leftarrow Enigma(m, nLess)$
- 8 **return** ans

Q # 02

Marks = [5+5+5]

- 2.1. In a warehouse management system, the inventory data is stored in a 2D array M of size $m_1 \times m_2$. Each row and column in the array is sorted in ascending order to optimize the lookup of items. Each element in M represents the stock quantity of a specific product. Given a target stock quantity k , you are tasked with determining whether the stock quantity exists in M .

Problem Statement:

Design an algorithm using the **Decrease (by a constant factor) and Conquer** strategy to search for k in the 2D array M . If k is found, return its position (i,j) , where i is the row index and j is the column index. If k is not found, return "Not Found."

Example:

$$M = \begin{bmatrix} 10 & 20 & 30 & 40 \\ 15 & 25 & 35 & 45 \\ 27 & 29 & 37 & 48 \\ 32 & 33 & 39 & 50 \end{bmatrix} \text{ and } k = 39$$

the algorithm should return (3,2)

If $k = 70$, the algorithm should return "Not Found."

- 2.2. Suppose you are working on a spell checker module of a software. Your program manager assigns you the following task:

Task: Let $W = w_1 w_2 \dots w_n$ be the misspell word of length n and $C = c_1 c_2 \dots c_m$ be the possible correct spell of W . Transform W into C with a minimum number of operations of the following types: delete a character from A , insert a character into A , or change some character in A .

The minimal number of such operations required to transform A into B is called the edit distance between A and B . Design an algorithm using **Dynamic Programming** that finds the edit distance from W to C .

- 2.3. Let T be the text file that we want to be sent over a network. Before sending the given text file we want to compress it. In order to compresses it as much as possible, we would like to find a binary code that encodes the file using as few bits as possible. The idea is to construct a binary tree based on the frequencies of characters in a given file. This tree is then used to generate variable-length codes for each character with shorter codes assigned to more frequently occurring characters.

Let $c_1, c_2, c_3, \dots, c_n$ denote the characters; $f_1, f_2, f_3, \dots, f_n$ be their frequencies respectively. Design an algorithm using **Greedy Approach** that efficiently encodes a set of symbols with variable-length codes, with the goal of minimizing the total number of bits required to represent a message.

Q # 03

Marks = [3+4]

- 3.1. State the **Loop Invariant**, $I(n)$ of the following algorithm.

ALGORITHM-2 *secret2*(y, z)

// Input: _____

// Output: _____

$x \leftarrow 0$

while $z > 0$ **do**

$x \leftarrow x + y * (z \% 2)$

$y \leftarrow 2 * y$

$z \leftarrow \lfloor z / 2 \rfloor$

end while

return x

- 3.2. Establish the **correctness** of the above algorithm using loop invariant that you define in part (3.1). Show all steps i.e., **initialization**, **maintenance** and **termination**.

Q # 04

Marks = [3+3+4]

- 4.1. Find the **time complexity** of the following code. Use most suitable asymptotic notation among O , Ω , and Θ to specify the time efficiency class of the given code.

```
void fun(int n)
{
    int j = 1, i = 0;
    while (i < n)
    {
        // Some O(1) task
        i = i + j;
        j++;
    }
}
```

- 4.2. Analyze the worst-case behavior of the following algorithm **COUNT3** by computing its **asymptotic upper bound**.

Algorithm COUNT3

Input: $n = 2^k$, for some positive integer k .

Output: *count* = number of times Step 5 is executed.

```
1. count ← 0
2. i ← 1
3. while i ≤ n
4.   for j ← 1 to i
5.     count ← count + 1
6.   end for
7.   i ← 2i
8. end while
9. return count
```

- 4.3. Analyze the worst-case behavior of the following recursive algorithm **Test**. Use appropriate asymptotic notation among O , Ω , and Θ to specify the time efficiency class of the given algorithm.

```
Test(n)
{
    m ← √n
    if(n = 1)
        return
    else
    {
        while(n < 1)
        {
            Print(n)
            n ← n/2
        }
        result ← Test(m) + Test(m)
    }
    return result
}
```

Q # 05

Marks = [3+2+3]

- 5.1. Given the following two scenarios, classify each as either **tractable** or **intractable**, and justify your reasoning:
- **Scenario 1:** Finding the shortest path between two locations on a road map.
 - **Scenario 2:** Determining the shortest possible route that visits each delivery location exactly once and returns to the starting point.
- 5.2. What does it mean for a problem to be NP-Complete? How is the concept of NP-Completeness related to the notion of polynomial-time reductions?
- 5.3. Let P_1 be an **NP-Complete** problem and P_2 and P_3 be two other problems not known to be in NP. P_2 is polynomial time reducible to P_1 and P_1 is polynomial-time reducible to P_3 . Explain which complexity class problem P_3 belongs to? Justify your answer.

Best of Luck